

Most Developed Heater featuring Double Clean Heat Chamber

FEATURES

- The Double Clean Heater reduces emission levels far below those of other kerosene heaters by the use of the Double Clean Heat Chamber. CO emissions are reduced by up to 15 times and NO2 by upt to 5 times compared to CPSC (= U.S. Government Agency) recommended level. Only Double Clean can claim the title as the world's clanest burning portable kerosene heater.
- TRIPLE SAFETY EXTINGUISHER There are 3 extinguishing methods on DC-100C.
 - 1. By retracting the wick
 - 2. By a simple touch of a lever
 - 3. Automatic shut-off is activated when the heater is bumped or in the event of a tip-over.
- HIGH EFFICIENCY The TOYOTOMI heater has 99.99% heat efficiency with Infrared-Ray heating.
- WICK LIFE EXTENDER This Wick Adjuster design lets you regulate wick for better performance. This additional control lengthens wick life up to three times and actually helps it heat more efficiently.
- DOUBLE WALL TANK CONSTRUCTION The Double Wall Tank Construction prevents leakage even when heater tips over for safety.



SPECIFICATIONS

MODEL: DC-100C

HEAT RATING: 17,500 BTU/h (5.15 kW/h)

FUEL CONSUMPTION: 0.501 lit./h
TANK CAPACITY: 7.5 lit.
BURNING TIME: 15 - 23 hrs.

DIMENSIONS (WxDxH): 474 x 474 x 560 mm

WEIGHT: 12.0 kg

TOYOTOMI CO., LTD.

5-17, MOMOZONO-CHO, MIZUHO-KU, NAGOYA, 467-0855 JAPAN

TEL: 81-52-822-1108, FAX: 81-52-824-7151

Website: www.toyotomi.jp

Printed in Japan #TB060057 Rev: 02/16
Subject to change with or without notice.