

Forced Flue Vented Type Heater

Model FF-95 (Type C)

FEATURES

■ CLEAN AND SAFE

“Pipe-within-a-pipe” forced flue venting system is a unique advanced heating system. The outside pipe of the venting system brings in outside air for combustion while the inner pipe exhausts all combustion by-products to the outside. The result is smokeless, odorless and clean heating. The unit also features automatically shut-off safety system.

■ EFFICIENT AND ECONOMICAL

Its special stainless steel heat exchanger carries the highest efficiency code and 92.4% heating efficiency. It surpasses oil and gas systems and is much more efficient and economical than wood stove.

■ CONVENIENT, EASY TO USE

This unit is one of the most advanced technologies with the economy of Kerosene heating. It features a simplified digital control panel that displays such as room temperature, temperature setting, time and error codes.

■ COMFORTABLE

The large circulation fan distributes clean heat quickly and evenly. The unit automatically regulates between low, medium and high burning modes. It turns itself off when the room temperature rises approx. 6 degrees above the desired set temperature, and it turns itself on automatically when the room temperature downs to the desired set temperature. (Power Saver Mode).

■ WEEKLY TIMER

The weekly timer can be programmed up to 30 patterns in a 24-hour period of the week. It is designed for energy efficiency by shifting automatically to a low burning mode or OFF, generally at night, and shifting automatically to ON and to a high burning mode, generally in the morning. You just need to set the time and a day before using.



SPECIFICATIONS

MODEL:	FF-95 (Type C)	
TYPE OF HEATER:	Forced Flue Vented Type Heater	
HEATING CAPACITY:	High: 32,400 BTU/h (9.50 kW/h), Med.: 18,700 BTU/h (5.49 kW/h) Low: 10,100 BTU/h (2.96 kW/h)	
FUEL CONSUMPTION:	High: 1.07 lit./h, Med.: 0.620 lit./h, Low: 0.334 lit./h	
HEATING EFFICIENCY:	92.4 %	
POWER SOURCE:	AC 220-230V, 50/60 Hz	
TYPE OF FUEL:	Paraffin only	
POWER CONSUMPTION:	Ignition: 260 W, Burning: 50 W	
NOISE LEVEL:	40 dB	
HEATER DIMENSIONS (WxDxH):	760 x 427 x 700 mm	
WEIGHT:	34 kg	
CONTAINER Q'TY (20FT / 40FT):	96 / 204 units	

TOYOTOMI CO., LTD.

5-17, Momozono-cho,
Mizuho-ku, Nagoya
467-0855 JAPAN
TEL: +81-52-822-1108
FAX: +81-52-824-7151
E-mail: ftd@toyotomi.jp
Website: www.toyotomi.jp

#TB170087 New: 02/17

Subject to change with or without notice