

Forced Flue Vented Type Heater

Model FQ-C70

TOYOTOMI

FEATURES

■ CLEAN AND SAFE

A circulation fan distributes the heat. The result is smokeless, odorless and clean heating. The unit also features shut-off safety system.

■ CONVENIENT, EASY TO USE

This unit is one of the most advanced technologies with the economy of Kerosene heating. It features a simplified digital control panel that displays such as room temperature, temperature setting, time and error codes.

■ COMFORTABLE

The large circulation fan distributes clean heat quickly and evenly. The unit automatically regulates between low, medium and high burn modes. It turns itself off when the room temperature rises approx. 2 degrees (2 °C) above the desired set temperature (SAVE mode).

■ SEMI-AUTOMATIC OPERATION

Features a 24-hour programmable timer and an integrated thermostat controller to maintain the desired room temperature. It offers 4 cycle burning modes (High ↔ Med. ↔ Low ↔ OFF).

■ ANTIQUE DESIGN

Traditional appearance and ceramic wood that is imaged fireplace are suited for pension, log house, living room and restaurant.

■ OVEN

When the heater operates in "HIGH" mode, the inside temperature will be approx. 180°C.
When the heater operates in "LOW" mode, the inside temperature will be approx. 100°C.



SPECIFICATIONS

MODEL:	FQ-C70
TYPE OF HEATER:	Forced Flue Vented Type Heater
HEATING CAPACITY:	High: 23,800 BTU/h (7.00 kW/h), Low: 7,400 BTU/h (2.18 kW/h)
FUEL CONSUMPTION:	High: 0.791 lit./h, Low: 0.246 lit./h
HEATING EFFICIENCY:	92.4 %
POWER SOURCE:	AC 220 V, 50 / 60 Hz
TYPE OF FUEL:	Kerosene only
POWER CONSUMPTION:	Ignition: 260 / 260 W, Burning: 55 / 52 W
HEATER DIMENSIONS (WxDxH):	840 x 450 x 745 mm
WEIGHT:	40 kg
CONTAINER Q'TY (20FT / 40FT):	48 / 100 units

TOYOTOMI CO., LTD.

5-17, Momozono-cho,
Mizuho-ku, Nagoya
467-0855 JAPAN
TEL: +81-52-822-1108
FAX: +81-52-824-7151
E-mail: ftd@toyotomi.jp
Website: www.toyotomi.jp

#TB180115 New: 02/18

Subject to change with or without notice