

Split Air Conditioner

Izuru series

FEATURES



SPECIFICATIONS

MODEL	INDOOR	TRN-828ZR	TRN-835ZR	TRN-856ZR	TRN-871ZR
	OUTDOOR	TRG-828ZR	TRG-835ZR	TRG-856ZR	TRG-871ZR
COOLING CAPACITY		9,212 BTU (2.70 kW)	11,942 BTU (3.50 kW)	17,742 BTU (5.20 kW)	23,884 BTU (7.00 kW)
HEATING CAPACITY		9,554 BTU (2.80 kW)	12,522 BTU (3.67 kW)	18,084 BTU (5.30 kW)	25,249 BTU (7.40 kW)
COOLING	SEER	6.8	7.0	7.0	6.5
	COOLING ENERGY CLASS	A++	A++	A++	A++
HEATING	SCOP AVERAGE ZONE	4.0	4.0	4.0	4.0
	ENERGY CLASS AVERAGE ZONE	A+	A+	A+	A+
	SCOP WARMER ZONE	5.1	5.1	5.1	5.1
	ENERGY CLASS WARMER ZONE	A+++	A+++	A+++	A+++
POWER SOURCE		220-240V, 50Hz			
DEHUMIDIFYING CAPACITY		0.8 L / h	1.4 L / h	1.8 L / h	2.4 L / h
COMPRESSOR		Rotary			
REFRIGERANT		R32			
DIMENSIONS (W x H x D)	INDOOR	866x367x271	921x379x281	1041x383x320	1148x413x350
	OUTDOOR	823x595x358	881x645x363	1029x750x458	1029x750x458
WEIGHT	INDOOR	11.0	12.5	16.5	20.0
	OUTDOOR	30.0	34.0	49.5	58.0
FEATURES		Meets the current European ErP directive, Higher energy efficiency, 8°C heating, Self clean function			

TOYOTOMI CO., LTD.

5-17, Momozono-cho,
Mizuho-ku, Nagoya
467-0855 JAPAN
TEL: +81-52-822-1108
FAX: +81-52-824-7151
E-mail: ftd@toyotomi.jp
Website: www.toyotomi.jp

#TB200131 New: 08/20

Subject to change with or without notice