

# TOYOTOMI

## CONVECTION TYPE KEROSENE HEATER Model KS-47

### FEATURES

#### ■ CLEAN COMBUSTION

The TOYOTOMI's state of the art Clean Chamber System maximizes fuel combustion and reduces carbon monoxide (CO) and other unwanted emission gases to very safety level.

#### ■ POWERFUL HEATING OUTPUT

It offers intense heating output up to 18,200 BTU / h.

#### ■ DURABLE CARBON GLASS FIBER WICK

Durable Carbon Glass Fiber Wick ensures a longer wick life-time than the cotton wick.

#### ■ WICK LIFE EXTENDER

TOYOTOMI's original patented design. It helps maintain good wick performance and extends useful wick life.

#### ■ TRIPLE SAFETY EXTINGUISHER

There are 3 extinguishing methods on KS-47.

1. Retracting the wick manually by the Main Knob (for wick adjuster): Reducing odor by long extinguishment (1 - 5 min.).
2. Simple touch of a Shut-off button: Extinguishment in short time (less than 10 sec.).
3. Automatic shut-off is activated when the heater is bumped or tips over: Safety system for earthquakes.

#### ■ SPARK IGNITION SYSTEM

This new uniquely designed spark ignition system is maintenance free and avoids any troubles caused by broken igniter coils, often found in conventional ignition system.

#### ■ DOUBLE WALL TANK CONSTRUCTION

The double wall tank construction prevents fuel leakage even when stove tips over for safety.

#### ■ MADE IN JAPAN

TOYOTOMI kerosene heaters are produced by our own factories in Japan.



### SPECIFICATIONS

<b>MODEL:</b>	KS-47
<b>HEATING RATING:</b>	18,200 BTU/h (5.35 kW/h)
<b>FUEL CONSUMPTION:</b>	0.520 L/h
<b>TANK CAPACITY:</b>	7.5 L
<b>BURNING TIME:</b>	Approx. 15 hrs.
<b>HEATER DIMENSIONS (WxDxH):</b>	440 x 440 x 582 mm
<b>ACCESSORIES:</b>	Manual Fuel Syphon pump, Butteries (Type C x 4 pcs.)
<b>CARTON DIMENSIONS (WxDxH):</b>	460 x 460 x 660 mm
<b>NET / GROSS WEIGHT:</b>	Approx. 9.5 / 11.0 kg
<b>CONTAINER Q'TY (20 / 40 / 40HC):</b>	215 / 450 / 520 units

#### TOYOTOMI CO., LTD.

5-17, MOMOZONO-CHO, MIZUHO-KU,  
NAGOYA, 467-0855 JAPAN  
TEL : 81-52-822-1108, FAX : 81-52-824-7151  
E-mail: [ftd@toyotomi.jp](mailto:ftd@toyotomi.jp)  
Website: [www.toyotomi.jp](http://www.toyotomi.jp)

Printed in Japan  
Subject to change with or without notice