

TOYOTOMI

ADVANCED TECHNOLOGY KEROSENE HEATER

FEATURES

■ TRIPLE SAFETY EXTINGUISHER

There are 3 extinguishing methods on RSX-2300.

1. Retracting the wick manually by the Main Knob (for wick adjuster)
2. Simple touch of a Shut-off button
3. Automatic shut-off is activated when the heater is bumped or in the event of a tip-over.

■ HIGH EFFICIENCY

The TOYOTOMI heater has 99.99% heat efficiency with Infrared-Ray heating.

The heater provides instant radiant heat.

■ SPARK IGNITION SYSTEM

Spark ignition system (named "ponPa") ignites the wick by discharging electrical spark between two electrodes, by simply just giving the Main Knob a full turn to the right.

This new uniquely designed spark ignition system is

maintenance free and avoids any troubles of igniter coils, often found in conventional heaters.

■ REMOVABLE FUEL TANK

Easy and convenient to refuel.

■ FUEL SIGN

You can see the fuel level at a glance.

When fuel tank is empty, fuel sign is indicated with orange color.



SPECIFICATIONS

MODEL:	RSX-2300
HEATING CAPACITY:	7,600 BTU/h (2.25 kW/h)
FUEL CONSUMPTION:	0.219 ℓ /h
TANK CAPACITY:	4.0 ℓ
BURNING TIME:	18 hrs.
DIMENSIONS (WxDxH):	422 x 330 x 446 mm
WEIGHT:	6.6 kg
CARTON SIZE (WxDxH):	465 x 370 x 505 mm
CONTAINER Q'TY (20 / 40 / 40HC):	312 / 640 / 800 units

Subject to change with or without notice.

TOYOTOMI CO., LTD.

5-17, MOMOZONO-CHO, MIZUHO-KU,
NAGOYA, 467-0855 JAPAN

TEL: 81-52-822-1108, FAX: 81-52-824-7151

E-mail: ftd@toyotomi.jp

Website: www.toyotomi.jp

#TB160010 New 11/16