

Kerosene Cooking Stove Model K-30FT

FEATURES

MULTIPLE FUNCTION

K-30FT is designed as Cooking purpose mainly. Due to powerful 2.25kW heating power, it is easy to cook as well as boiling the water. Furthermore, it can be used as a space heating in the house. It is also very useful in a time of disaster when life line is cut off.

DOUBLE WALL TANK CONSTRUCTION The double wall tank construction delays fuel leakage even when stove tips over for safety.

DURABLE GLASS FIBER WICK Durable Glass Fiber Wick ensures a longer wick lifetime than cotton wick. Glass Fiber Wick cannot be burned out easily even if the stove runs out the fuel. Tar deposit on the wick can be removed cleanly by the method of burning dry.

■ EASY TO OPERATE AND MAINTAINANCE Just turn the knob clockwise and ignite with a match or a lighter. Then turn the knob counterclockwise for turn-off. No tool is required to replace a wick and it is easy for maintenance.



SPECIFICATIONS

MODEL: TYPE OF HEATER: IGNITION: HEATING CAPACITY: FUEL CONSUMPTION: TYPE OF FUEL: FUEL TANK CAPACITY: BURNING TIME: HEATER DIMENSIONS (WxDxH): WEIGHT (Net): CONTAINER Q' TY (20FT / 40FT): K-30FT Cooking / Heating Stove Manual by match 2.25 kW/h (7,600BTU/h) 0.209 lit. /h Kerosene 4.0 lit 19.1 hours 343 x 343 x 329 mm 3.5 kg 540 / 1116 units.

TOYOTOMI CO., LTD.

5-17, Momozono-cho, Mizuho-ku, Nagoya 467-0855 JAPAN TEL: +81-52-822-1108 FAX: +81-52-824-7151 E-mail: ftd@toyotomi.jp Website: www.toyotomi.jp

#TB110801 Rev. 02/16

Subject to change with or without notice