

Wick Type Kerosene Heater Model KS-27A

FEATURES

■ CLEAN COMBUSTION SYSTEM
The TOYOTOMI's state of the art Clean Chamber
System maximizes fuel combustion and reduces
carbon monoxide (CO) and other unnecessary
emission gases to very safety level.

■ TRIPLE SAFETY EXTINGUISHER

There are 3 extinguishing methods on KS-27A.

- 1. By retracting the wick
- 2. By a simple touch of a lever
- 3. Automatic shut-off is activated when the heater is bumped or in the event of a tip-over.

■ HIGH EFFICIENCY The TOYOTOMI heater has 99.99% heat efficiency with Infrared-Ray heating.

■ DOUBLE WALL TANK CONSTRUCTION The Double Wall Tank Construction prevents

leakage even when heater tips over for safety.



SPECIFICATIONS

MODEL: KS-27A

TYPE OF HEATER: Wick Type Kerosene Heater HEATING CAPACITY: 10,000 BTU/h (2.94 kW)

FUEL CONSUMPTION: 0.286 lit./h
TYPE OF FUEL: Kerosene only

FUEL TANK CAPACITY: 6.3 L BURNING TIME: 22 hours

HEATER DIMENSIONS (WxDxH): 440 x 440 x 470 mm

PRODUCT WEIGHT: 7.7 kg

CONTAINER Q'TY (20FT / 40FT): 275 / 575 units

TOYOTOMI CO., LTD.

5-17, Momozono-cho, Mizuho-ku, Nagoya 467-0855 JAPAN TEL: +81-52-822-1108 FAX: +81-52-824-7151

FAX: +81-52-824-7151 E-mail: ftd@toyotomi.jp Website: www.toyotomi.jp

#TB080717 Rev. 02/16

Subject to change with or without notice