

TOYOTOMI

CONVECTION TYPE KEROSENE HEATER Model RB-250

FEATURES

■ CLEAN COMBUSTION

The TOYOTOMI's state of the art Clean Chamber System maximizes fuel combustion and reduces carbon monoxide (CO) and other unwanted emission gases to very safety level.

■ DURABLE CARBON GLASS FIBER WICK

Durable Carbon Glass Fiber Wick ensures a longer wick life-time than the cotton wick.

■ TRIPLE SAFETY EXTINGUISHER

There are 3 extinguishing methods on RB-250.

1. Retracting the wick manually by the Main Knob: Reducing odor by long extinguishment (1 - 5 min.).
2. Simple touch of a Shut-off button: Extinguishment in short time (less than 10 sec.).
3. Automatic shut-off is activated when the heater is bumped or tips over: Safety system for earthquakes.

■ SEVEN COLOR SHINING FLAME

The special coated glass makes your room lighter (approx. 40W of light) with seven color flame.

■ SPARK IGNITION SYSTEM


This new uniquely designed spark ignition system is maintenance free and avoids any troubles caused by broken igniter coils, often found in conventional ignition system.

■ DOUBLE WALL TANK CONSTRUCTION

The double wall tank construction prevents fuel leakage even when heater tips over for safety.

■ MADE IN JAPAN

TOYOTOMI kerosene heaters are produced by our own factories in Japan.



SPECIFICATIONS

MODEL:	RB-250
HEATING CAPACITY:	8,500 BTU/h (2.50 kW/h) – 4,300 BTU/h (1.25 kW/h)
FUEL CONSUMPTION:	0.243 L/h – 0.122 L/h
TANK CAPACITY:	4.9 L
BURNING TIME:	Approx. 20 - 40 hrs.
HEATER DIMENSIONS (WxDxH):	388 x 388 x 474.5 mm
ACCESSORIES:	Manual Fuel Syphon Pump, Batteries (Type C x 4 pcs.)
CARTON DIMENSIONS (WxDxH):	420 x 420 x 510 mm
NET / GROSS WEIGHT:	Approx. 6.2 / 7.5 kg
CONTAINER Q'TY (20 / 40 / 40HC):	323 / 655 / 756 units

TOYOTOMI CO., LTD.

5-17, MOMOZONO-CHO, MIZUHO-KU,
NAGOYA, 467-0855 JAPAN
TEL : 81-52-822-1108, FAX : 81-52-824-7151
E-mail: ftd@toyotomi.jp
Website: www.toyotomi.jp

Printed in Japan
Subject to change with or without notice