

TOYOTOMI

Newest Developed Heater with High Efficiency and Advanced Safety Features

FEATURES

■ CLEAN COMBUSTION

The TOYOTOMI's state of the art Clean Chamber System maximizes fuel combustion and reduces carbon monoxide (CO) and other unwanted emission gases to very safety level.

■ HIGH EFFICIENCY

The TOYOTOMI heater has 99.99 % heat efficiency with Infrared-ray heating.

■ AUTOMATIC IGNITION

Easy to turn on the heater by turn right the dial.

■ TRIPLE SAFETY EXTINGUISHER

There are 3 extinguishing methods on RCA-37.

1. By retracting the wick.
2. By a simple button pushing.
3. Automatic shut-off is activated when the heater is bumped or in the event of a tip-over.

■ POWERFUL HEATING OUTPUT

It offers intense heating output up to 10,300 BTU / h.

■ WICK LIFE EXTENDER

TOYOTOMI's original patented design. It helps maintain good wick performance and extends useful wick life.

■ SPARK IGNITION SYSTEM

Spark ignition system ignites the wick by discharging electricity between two electrodes, by simply just giving the main knob (for wick adjuster) a full turn to the right. This new uniquely designed spark ignition systems is maintenance free and avoids any troubles caused by broken igniter coils, often found in convetional ignition systems.

■ ECONOMICAL

Easy to ignite and low running cost with less fuel.

■ EASY TO FILL

Convenient removable fuel tank and a handy syphon comes with the heater.



SPECIFICATIONS

MODEL:	RCA-37
HEAT RATING:	10,300 BTU/h (3.02 kW/h)
FUEL CONSUMPTION:	0.294 L/h
TANK CAPACITY:	4.7 L
BURNING TIME:	Approx. 16.8 hrs.
HEATER DIMENSIONS (W x D x H):	586 x 304 x 439 mm
CARTON DIMENSIONS (W x D x H):	630 x 345 x 510 mm
WEIGHT:	Approx. 10.8 kg
CONTAINER Q'TY (20 / 40 / 40HC):	280 / 585 / 643 units

TOYOTOMI CO., LTD.

5-17, MOMOZONO-CHO, MIZUHO-KU,
NAGOYA, 467-0855 JAPAN
TEL : 81-52-822-1108, FAX : 81-52-824-7151
E-mail: ftd@toyotomi.jp
Website: www.toyotomi.jp

Printed in Japan
Subject to change with or without notice