

TOYOTOMI

ADVANCED TECHNOLOGY KEROSENE HEATER Model RS-W30

FEATURES

■ CLEAN COMBUSTION

The TOYOTOMI's state of the art Clean Chamber System maximizes fuel combustion and reduces carbon monoxide (CO) and other unwanted emission gases to very safety level.

■ POWERFUL HEATING OUTPUT

It offers intense heating output up to 10,300 BTU / h.

■ DURABLE CARBON GLASS FIBER WICK

Durable Carbon Glass Fiber Wick ensures a longer wick life-time than the cotton wick.

■ WICK LIFE EXTENDER

TOYOTOMI's original patented design. It helps to maintain good wick performance and extends useful wick life.

■ TRIPLE SAFETY EXTINGUISHER

There are 3 extinguishing methods on RS-W30.

1. Retracting the wick manually by the Main Knob:
Reducing odor by long extinguishment (1 - 5 min.).
2. Simple touch of a Shut-off button:
Extinguishment in short time (less than 10 sec.).
3. Automatic shut-off is activated when the heater is bumped or tips over: Safety system for earthquakes.

■ SPARK IGNITION SYSTEM

This new uniquely designed spark ignition system is maintenance free and avoids any troubles of igniter coils, often found in conventional heaters.

■ MADE IN JAPAN

TOYOTOMI kerosene heaters are produced by our own factories in Japan.



SPECIFICATIONS

MODEL:	RS-W30
HEATING CAPACITY:	10,300 BTU/h (3.02 kW/h)
FUEL CONSUMPTION:	0.294 L/h
TANK CAPACITY:	4.7 L
BURNING TIME:	Approx. 16 -19 hrs.
HEATER DIMENSIONS (WxDxH):	586 x 304 x 439 mm
ACCESSORIES:	Manual Fuel Syphon Pump, Batteries (Type C x 4 pcs.)
CARTON DIMENSIONS (WxDxH):	620 x 330 x 510 mm
NET / GROSS WEIGHT:	Approx. 9.0 / 11.0 kg
CONTAINER Q'TY (20 / 40 / 40HC):	252 / 532 / 665 units

TOYOTOMI CO., LTD.

5-17, MOMOZONO-CHO, MIZUHO-KU,
NAGOYA, 467-0855 JAPAN
TEL : 81-52-822-1108, FAX : 81-52-824-7151
E-mail: ftd@toyotomi.jp
Website: www.toyotomi.jp

Printed in Japan
Subject to change with or without notice