

Compressor Type Dehumidifier

Model TD-C100

TOYOTOMI

FEATURES

- **COMPRESSOR TYPE DEHUMIDIFIER**
This model features compressor instead of desiccant.
Accordingly this model shows great ability in the areas of High-temperature and humidify.
- **HIGH EFFICIENT COMPRESSOR**
High efficient rotary compressor runs at low energy consumption.
- **HIGH EFFICIENT DC MOTOR**
High efficient DC motor runs at low energy consumption and at big dehumidifying capacity.
- **DUAL WATER DRAINAGE OPTION**
 - Continuous drainage by connecting hose from the unit
 - 2.0 L water tank
- **COMPACT BODY & LIGHTWEIGHT**
Model TD-C100 is compact design.
It is very convenient to carry around with handle.
- **AUTOMATIC OPERATION**
Room humidity can be controlled automatically by setting the desired humidity.
- **4 MODE DEHUMIDIFY CONTROL: 40% / 50% / 60% / Cont.**



SPECIFICATIONS

MODEL:	TD-C100
APPLICABLE SPACE:	41.6 m ²
DEHUMIDIFYING CAPACITY:	10 L/day (30°C/ 80% RH)
POWER SOURCE:	Single phase 220~240V / 50Hz
OPERATION TEMPERATURE RANGE:	5 °C - 32 °C
POWER CONSUMPTION:	205 W
COMPRESSOR:	Rotary
REFRIGERANT:	R-134A
PRODUCT DIMENSIONS (W x H x D):	230 x 386 x 230 mm
CONTAINER Q'TY (20FT / 40FT / 40HQ):	910 / 1845 / 2273 units
WEIGHT:	8.5kg

TOYOTOMI CO., LTD.

5-17, Momozono-cho,
Mizuho-ku, Nagoya
467-0855 JAPAN
TEL: +81-52-822-1108
FAX: +81-52-824-7151
E-mail: ftd@toyotomi.jp
Website: www.toyotomi.jp

#TB140076 Rev.: 03/16

Subject to change with or without notice